

*Call for custom lamp / custom base or OEM project requests



Image	Order Code	Description	Other Detail	V	W	Base	Life Hr	Lumen	CP	MOL (mm)	LCL (mm)	Dia (mm)	Bulb Shape	Filament
A-1-1962DZ	A-1962DZ	JC 8.5V 62W Wire Terminal (1962DZ)	1962DZ	8.5	62	Wire Terminal	150		80	1.14in	0.285in	11	T-3	C-6
A-1-1962TY	A-1962TY	JC 8.5V 62W Wire Terminal(7.75") (1962TY)	1962TY	8.5	62	Wire Terminal(7-3/4")	50		110	1.14in	0.285in	11	T-3	C-6
A-1-1974	A-1974	JC 6V 20W Wire Terminal (1974)	1974	6	20	Wire Terminal	10000		10	1.14in	0.285in	11	T-3	C-6
A-2	A-6517	J 10V 100W Metal Base (1978X)	1978X	10	100	Metal Base	1000	1633	130	54.6(2.15in)		9	T21/2	C-8
A-3	A-1975	JC 12.8V 25W Double Slide (1975)	1975	12.8	25	Double Slide	500	314	25	29.7(1.17in)	11.2(0.41in)	11	T-3	C-6
A-4	A-6519	J 28V 100W Metal Sleeve (1970X)	1970X	28	100	Metal Sleeve	2000	1260	140	57.1(2.25in)		9	T21/2	CC-8
A-4	A-1964	J 28V 150W Metal Sleeve (1964)	1964	28	150	Metal Sleeve	1000		230	2.25in		11	T-3	CC-8
A-4	A-6527	J 28V 150W Metal Sleeve (1967)	1967	28	150	Metal Sleeve	1000	2600	210	57.1(2.25in)		9	T21/2	CC-8
A-5	A-6521	JC 28V 75W BA15S (1982)	1982	28	75	BA15s	2000	1300	110	48.0(1.88in)	27.0(1.06in)	11	T-3	CC-8
B-1	A-1959	J 28V 150W Tab (1959)	1959	28	150	Tab	300		240	2.25in	0.75in	13.5	T-4	CC-6
B-2	A-1945	JC 32V 200W Two Pin (1945)	1945	32	200	Two Pin	200		360	57.15(2.25in)	33.27(1.31in)	13.5	T-4	CC-6
B-3	A-1946	28V 250W Two Pin w/leads (1946)	1946	28	250	Two Pin w/Leads	50		660	1.46in	0.87in	11	T-3	CC-6
B-6	TBD	JC 28V 250W Two Pin w/leads (2586)	2586	28	250	Two Pin Leads	100		600	1.9in	1.3in	13.5	T-4	CC-6
C-13	A-6511	JC 12V 125W 10H BA15d (6511)	6511	12V	125	BA15d	750	2400	191	54.0(2.125in)	27.5(1.08in)	11	T3	C-8
C-13	A-6513	JC 24V 150W 5H BA15d		24V	150	BA15d								
C-13	A-6503	JC 28V 150W BA15d (6503)	6503	28V	150	BA15d	750	3300	263	54.0(2.125in)	27.5(1.08in)	11	T3	CC-8
C-3-SO14040	S-01026	JC 12V 20W GY9.5 (S014040)	S014040	12V	20	GY9.5	2000	300	24	51.0(2in)	30	11	T3	C-6
NA	A-1912	12V 125W BA15D (1912)	1912	12	125	BA15d	1000		191	1.93in	1.14in	13.5	T-4	CC-8
NA	A-6515	JC 26V 150W 5H BCD		26V	150	BA15d								
NA	A-6527L	JC 28V 10.5W BA9s BT		28V	10.5	BA9s/Black Top	2500		130 lm	1.3in	0.59in	9	T2	C-8
NA	A-6530L	JC 28V 10.5W BA9s CL		28V	10.5	BA9s/Clear Top	2500		130 lm	1.3in	0.59in	9	T2	C-8



C-1



C-10



C-11



C-12



C-2



C3-EVV



C-4



C-5



C-6



C-7



C-8



C-9

Image	Order Code	Description	Other Detail	V	W	Base	Life Hr	Lumen	CP	MOL (mm)	LCL (mm)	Dia (mm)	Bulb Shape	Filament
C-1	A-6331	JF 6.6A 30W GY9.5 (EXL)	EXL	6.6 Amp	30	GY9.5	1000	380	30	44.0(1in)	25.5(1.732in)	11	T3	C-8
C-1	A-6327	JF 6.6A 45W-B GY9.5 (EXM)	EXM	6.6 Amp	45	GY9.5	1000	750	60	44.0(1in)	25.5(1.732in)	11	T3	C-8
C-10	A-6315	JF 6.6A 45W DCR P30D (6315)	6315, 6.6A	6.6 Amp	45	DC Reverse Ring P30D	1000	800 lm		2.5in	1.063in	13.5	T4	C-8
C-11	A-6319	JF 6.6A 115W DCR P30D (6319)	6319, 6.6A	6.6 Amp	115	DC Reverse Ring P30D	500	2800 lm		2.489in	1.063in	13.5	T4	C-6
C-12	A-6323	JF 6.6A 185W DCR P30D (6323)	6323, 6.6A	6.6 Amp	185	DC Reverse Ring P30D	500	4400 lm		2.362in	1.063in	13.5	T4	CC-6
C-12	A-6317	JF 6.6A 200W DCR P30D (6317)	6317, 6.6A	6.6 Amp	200	DC Reverse Ring P30D	500	4800 lm		2.362in	1.063in	13.5	T4	CC-6
C-2	A-6329	JF 6.6A 150W-B GY9.5 (EWR)	EWR	6.6 Amp	150	GY9.5	500	3600	285	65.0(1.535in)	39.0(2.56in)	13.5	T4	CC-6
C-2	A-6325	JF 6.6A 200W-B GY9.5 (EZL)	EZL	6.6 Amp	200	GY9.5	500	4800	380	65.0(1.535in)	39.0(2.56in)	13.5	T4	CC-6
C-3-EVV	A-6343	JF 6.6A 115W-B GY9.5 (EVV)	EVV	6.6 Amp	115	GY9.5	500	2500	200	65.0(1.535in)	39.0(2.56in)	13.5	T4	C-6
C-4	A-6301	JF 6.6A 30W PK30d		6.6 Amp	30	PK30d	1000	377	30	37.0(0.63in)	16.0(1.457in)	13.5	T4	C-8
C-4	A-6303	JF 6.6A 45W PK30d		6.6 Amp	45	PK30d	1000	630	50	37.0(0.63in)	16.0(1.457in)	13.5	T4	C-8
C-4	A-6303F	JF 6.6A 45W PK30d W/FEMALE ENDS		6.6 Amp	45	PK30d Female End	1000	630	50	37.0(0.63in)	16.0(1.457in)	13.5	T4	C-8
C-5	A-6305	JF 6.6A 100W PK30d		6.6 Amp	100	PK30d	1000	2200	175	43.0(0.787in)	20.0(1.693in)	13.5	T4	C-6
C-6	A-6309	JF 6.6A 150W PK30d		6.6 Amp	150	PK30d	1000	3600	285	43.0(0.787in)	20.0(1.693in)	13.5	T4	CC-6
C-6	A-6313	JF 6.6A 200W PK30d		6.6 Amp	200	PK30d	1000	4800	380	43.0(0.787in)	20.0(1.693in)	13.5	T4	CC-6
C-6	A-6313F	JF 6.6A 200W PK30d W/FEMALE ENDS		6.6 Amp	200	PK30d Female End	1000	4800	380	43.0(0.787in)	20.0(1.693in)	13.5	T4	CC-6
C-7	A-6333	JF 6.6A 45W R7s		6.6 Amp	45	R7s	1000	630	50	52.0(2.047in)		9	T21/2	C-8
C-7	A-6339AL	JF 6.6A 100W/R7s Alumimum Base		6.6 Amp	100	R7s Alumi.	1000		170	2.311in		11	T3	C-8
C-8	A-6335	JF 6.6A 100W-2 R7s		6.6 Amp	100	R7s	1000	2120	170	63.6(2.504in)		11	T3	CC-8
C-8	A-6339	JF 6.6A 100W R7s		6.6 Amp	100	R7s	1000	2120	170	63.6(2.504in)		11	T3	CC-8
C-8	A-6337	JF 6.6A 200W R7s		6.6 Amp	200	R7s	1000	4240	340	63.6(2.504in)		11	T3	CC-8
C-9	A-6341	JF 6.6A 100W Wire		6.6 Amp	100	Lead Wire	1000	2120	170	50.0(1.969in)		11	T3	CC-8
C-9	A-6347	JF 6.6A 200W Wire		6.6 Amp	200	Lead Wire	1000	4240	340	50.0(1.969in)		11	T3	CC-8

CROSS REFERENCE

Image	Order Code	Description	Cross Ref # 1	Cross Ref	Cross Ref # 2
A-1-1962DZ	A-1962DZ	JC 8.5V 62W Wire Terminal (1962DZ)	1962DZ		
A-1-1962TY	A-1962TY	JC 8.5V 62W Wire Terminal(7.75") (1962TY)	1962TY		
A-1-1974	A-1974	JC 6V 20W Wire Terminal (1974)	1974		
A-2	A-6517	J 10V 100W Metal Base (1978X)	1978X	Osram	54937
A-3	A-1975	JC 12.8V 25W Double Slide (1975)	1975		
A-4	A-6519	J 28V 100W Metal Sleeve (1970X)	1970X	Osram	54936
A-4	A-1964	J 28V 150W Metal Sleeve (1964)	1964		
A-4	A-6527	J 28V 150W Metal Sleeve (1967)	1967		
A-5	A-6521	JC 28V 75W BA15S (1982)	1982		
B-1	A-1959	J 28V 150W Tab (1959)	1959		
B-2	A-1945	JC 32V 200W Two Pin (1945)	1945		
B-3	A-1946	28V 250W Two Pin w/leads (1946)	1946		
B-6	TBD	JC 28V 250W Two Pin w/leads (2586)	2586		
C-13	A-6511	JC 12V 125W 10H BA15d (6511)	040-0028A		
C-13	A-6513	JC 24V 150W 5H BA15d			
C-13	A-6503	JC 28V 150W BA15d (6503)	040-0003		
C-3-S014040	S-01026	JC 12V 20W GY9.5 (S014040)	Gil Way	L9404	
NA	A-1912	12V 125W BA15D (1912)	1912		
NA	A-6515	JC 26V 150W 5H BCD			
NA	A-6527L	JC 28V 10.5W BA9s BT	64301X	WelchAll	998502-14
NA	A-6530L	JC 28V 10.5W BA9s CL			

Image	Order Code	Description	Cross Ref	Cross Ref # 1	Cross Ref	Cross Ref # 2	Cross Ref	Cross Ref # 3
C-1	A-6331	JF 6.6A 30W GY9.5 (EXL)	Osram	64322			Philips	6112
C-1	A-6327	JF 6.6A 45W-B GY9.5 (EXM)	Osram	64320	GE	41541	Philips	6134
C-10	A-6315	JF 6.6A 45W DCR P30D (6315)	Crouse H	20553				
C-11	A-6319	JF 6.6A 115W DCR P30D (6319)	Crouse H	20496				
C-12	A-6323	JF 6.6A 185W DCR P30D (6323)	Crouse H	20538				
C-12	A-6317	JF 6.6A 200W DCR P30D (6317)	Crouse H	20531				
C-2	A-6329	JF 6.6A 150W-B GY9.5 (EWR)	Osram	64354	Philips	6292		
C-2	A-6325	JF 6.6A 200W-B GY9.5 (EZL)	Osram	58750	Philips	6372		
C-3-EVV	A-6343	JF 6.6A 115W-B GY9.5 (EVV)	Osram	58798	Crouse H	20058	Philips	6128
C-4	A-6301	JF 6.6A 30W PK30d						
C-4	A-6303	JF 6.6A 45W PK30d	Osram	58705	Osram	64317	Philips	6303
C-4	A-6303F	JF 6.6A 45W PK30d W/FEMALE ENDS						
C-5	A-6305	JF 6.6A 100W PK30d	Osram	58706	Osram	64342	Philips	6312
C-6	A-6309	JF 6.6A 150W PK30d	Osram	64361				
C-6	A-6313	JF 6.6A 200W PK30d	Osram	58708	Osram	64382	Philips	6313
C-6	A-6313F	JF 6.6A 200W PK30d W/FEMALE ENDS						
C-7	A-6333	JF 6.6A 45W R7s	GE	23846	Osram	58704	Osram	64315
C-7	A-6339AL	JF 6.6A 100W/R7s Alumimum Base						
C-8	A-6335	JF 6.6A 100W-2 R7s	GE	23853				
C-8	A-6339	JF 6.6A 100W R7s						
C-8	A-6337	JF 6.6A 200W R7s			Osram	58707	Osram	64380
C-9	A-6341	JF 6.6A 100W Wire	GE	23855				
C-9	A-6347	JF 6.6A 200W Wire			Osram	58800		